
















Référence	Produit	Description du produit	Driver	Angle	W	Lm	Prix € HT départ/unité	Années de garantie
Fixed Explosion Proof Light								
BC5401-L2*20 ceiling mounting	 LED	Ex code: II2GD Ex de op IIC T5 Gb,Ex op is tb IIIC T95°C, Db,IP66 Input voltage: 90 to 264VAC LED Chip:Epistar SMD (T8,1200 mm) LED light source life: More than 50,000 hours material: aluminium alloy body; stainless steel cover and mesh,screws. net weight: 12kgs Certificae: CE,ROHS,ATEX,CNEX	/	120°	2*20W	3841lm	595 €	3 yrs
BC5401-L2*10 ceiling mounting	 LED	Ex code: II2GD Ex de op IIC T5 Gb,Ex op is tb IIIC T95°C Db,IP66 Input voltage: 90 to 264VAC LED Chip:Epistar SMD (T8,600mm) LED light source life: More than 50,000 hours material: aluminium alloy body; stainless steel cover and mesh,screws. net weight:7.5kgs Certificae: CE,ROHS,ATEX,CNEX	/	120°	2*10W	1880lm	497 €	3 yrs
BC5401-L2X10-J	 120 minute	Ex code: II2GD Ex de op IIC T5 Gb,Ex op is tb IIIC T95°C Db,IP66 Input voltage: 90 to 264VAC LED Chip:Epistar SMD LED light source life: More than 50,000 hours material: aluminium alloy body; stainless steel cover and mesh,screws. net weight:6.6kgs lamp/ 2.9kgs emergency box Certificae: CE,ROHS,ATEX,CNEX			2x10w normal light/ 10w emergency light	1800lm	871 €	3 yrs










Référence	Produit	Description du produit	Driver	Angle	W	Lm	Prix € HT départ/unité	Années de garantie
BC5401-L2X20-J	 60minutes	Ex code: II2GD Ex de op IIC T5 Gb,Ex op is tb IIIC T95°c Db,IP66 Input voltage: 90 to 264VAC LED Chip:Epistar SMD LED light source life: More than 50,000 hours material: aluminium alloy body; stainless steel cover and mesh,screws. net weight: 10.7kgs lamp/ 2.9kgs emergency box Certificae: CE,ROHS,ATEX,CNEX			2x20w normal light/ 20w emergency light	3341lm	968 €	3 yrs
BC5402B-L20		Product name:LED linear light Light Source: Lumileds LED SMD Input Voltage:108-264VAC Frequency:50Hz/60Hz IP66/IP67 Ex mark : Ex nR IIC T6 Gc Material: aluminium alloy +pc cover net weight: 3.4kgs for 20w,30w,40w; 4.5kgs for 60w,80w	inventronic	20W	2200	700x182x68mm	401 €	3 yrs
BC5402B-L30				30w	3300	700x182x68mm	416 €	3 yrs
BC5402B-L40				40W	4400	700x182x68mm	432 €	3 yrs
BC5402B-L60				60W	6600	1150x182x68mm	640 €	3 yrs
BC5402B-L80				80W	8800	1150x182x68mm	663 €	3 yrs
			emergency wattage and time					3 yrs
BC5402BJ-L20		Product name:LED linear light Light Source: Lumileds LED SMD IP66/IP67 Input Voltage:108-264VAC Frequency:50Hz/60Hz Ex mark : Ex e mb IIC T6 Gb Material: aluminium alloy +pc cover net weight: 3.4kgs for 20w,30w,40w; 4.5kgs for 60w,80w	15w 150min		20W	700x182x68mm	491 €	3 yrs
BC5402BJ-L30				25w 90min	30W	700x182x68mm	566 €	3 yrs
BC5402BJ-L40				25w 90min	40W	700x182x68mm	618 €	3 yrs
BC5402BJ-L60				25w 90min	60w	1150x182x68mm	805 €	3 yrs
BC5402BJ-L80				25w 90min	80w	1150x182x68mm	848 €	3 yrs
						Emergency time		
BXP01		Ex Marking: II2 GD Ex db e IIC T5/T6 Gb Ex tb IIIC T95°c/ T80 Db ,IP66 Input voltage: 90-264VAC output voltage:220VDC,			40W	45min	374 €	3 yrs
					20W	900min	374 €	3 yrs



















Référence	Produit	Description du produit	Driver	Angle	W	Lm	Prix € HT départ/unité	Années de garantie
		Net weight: 2.9kgs,size: 238x222x106mm Certificate:ATEX			10W	180min	374 €	3 yrs
BHD01A/BHD01B		Name: explosion proof junction box. Ex: II2 GD Ex db IIC T6 Gb Ex tb IIC T80°c Db IP66 Input voltage range: 500v rate frequency: 50hz/60hz rated current:<20A. Core section: 0.5~2.m ^m Cable entry: BHD01A: G3/4" ; BHD01B,BHD02: M25X1.5,M20X1.5,NPT3/4",NPT1/2". Weight: 1.2kgs: BHD01A,BHD01B; 0.8KGS: BHD02 Certificate:INERIS 16ATEX0008X IECEX INE 16.0017X					71 €	5yrs
BHD02							76 €	5yrs
BC9306P-L30 (30W LED, pole mounting)		Product name:Explosion-proof LED lamp Ex Marking:Ex db e IIC T6...T3 Gb Ex tb IIC T80°c...T195°c Db ,IP66 Cable entry:M20 M25 NPT3/4 NPT1/2 G3/4 light source: Citizen 1pc Input voltage: AC90-264V(30W-80W) 18~43VAC(30W-60W), 18~55VDC(30-60W) color temperature(CCT):5000k light source service life:50,000 hrs material:Special Aluminium Alloy size:230mm*270mm Net weight:4.2kgs Certificae: CE,ATEX,CNEX	Light Driver: Taiwan Meanwell	40°, 60°, 80°, 100°, 200°, 60*80°, 90°*110°	30W	3500lm	546 €	5yrs
BC9306P-L40 (40W LED, pole mounting)					40W	4600lm	573 €	5yrs
BC9306P-L50 (50W LED, pole mounting)					50W	5600lm	670 €	5yrs
BC9306P-L60 (60W LED, pole mounting)					60W	7000lm	726 €	5yrs
BC9306P-L80 (80W LED, pole mounting)					80W	8800lm	871 €	5yrs
BC9306S-L30 (30W LED, Bracket mounting)		Product name:Explosion-proof LED lamp Ex Marking:Ex db e IIC T6...T3 Gb Ex tb IIC T80°c..T195°c Db ,IP66 Cable entry:M20 M25 NPT3/4 NPT1/2 G3/4 light source: Citizen 1pc Input voltage: AC90-264V(30W-80W) 18~43VAC(30W-60W), 18~55VDC(30-60W) color temperature(CCT):5000k light source service life:50,000 hrs material:Special Aluminium Alloy	Light Driver: Taiwan Meanwell	40°, 60°, 80°, 100°, 200°, 60*80°, 90°*110°	30W	3500lm	582 €	5yrs
BC9306S-L40 (40W LED, bracekt mounting)					40W	4600lm	607 €	5yrs
BC9306S-L50 (50W LED, bracket mounting)					50W	5600lm	704 €	5yrs
BC9306S-L60 (60W LED, bracket mounting)					60W	7000lm	759 €	5yrs

Référence	Produit		Description du produit	Driver	Angle	W	Lm	Prix € HT départ/unité	Années de garantie
BC9306S-L80 (80W LED, bracket mounting)			size:245mm*260mm*270mm Net weight:4.9kgs Certificae: CE,ATEX,CNEX	Light Driver: Inventronics		80W	8800lm	905 €	5yrs
BC9306S-L30 -18° (30W LED, bracket mounting)			Product name:Explosion-proof LED lamp Ex Marking:Ex db e IIC T6...T3 Gb Ex tb IIC T80°c..T195°c Db ,IP66 Cable entry:M20 M25 NPT3/4 NPT1/2 G3/4 light source: Citizen 1pc Input voltage: AC90-264V(30W-80W) 18~43VAC(30W-60W), 18~55VDC(30-60W) color temperature(CCT):5000k light source service life:50,000 hrs material:Special Aluminium Alloy size:245mm*260mm*270mm size:245mm*260mm*270mm Net weight:5.3kgs Certificae: CE,ATEX,CNEX	Taiwan Meanwell	18°	30W	3500lm	642 €	5yrs
BC9306S-L40 -18° (40W LED, bracekt mounting)						40W	4600lm	670 €	5yrs
BC9306S-L50 -18° (50W LED, bracket mounting)						50W	5600lm	769 €	5yrs
BC9306S-L60 -18° (60W LED, bracket mounting)						60W	7000lm	820 €	5yrs
BC9306S-L80 -18° (80W LED, bracket mounting)						80W	8800lm	1 019 €	5yrs
BC9306S-L80 -18° (80W LED, bracket mounting)				Light Driver: Inventronics		80W	8800lm	1 019 €	5yrs
BC9306AP-L40-15	Normal illuminate+E emergency	140 minute	Product name:Explosion-proof LED lamp Ex Marking:Ex db e IIC T6...T3 Gb Ex tb IIC T80°c...T195°c Db ,IP66 Cable entry:M20 M25 NPT3/4 NPT1/2 G3/4 light source: Citizen 1pc Input voltage: AC90-264V color temperature(CCT):5000k light source service life:50,000 hrs material:Special Aluminium Alloy size:245mm*260mm*270mm Net weight:5.3kgs Certificae: CE,ATEX,CNEX	Light Driver: Taiwan Meanwell	40°, 60°, 80°, 100°, 200°, 60*80°, 90°*110°	40W	1800lm	670 €	3 yrs
BC9306AP-L40-25		70 minute				40W	3300lm	670 €	3 yrs
BC9306BP-15	Only Emergency	140 minute				15W	1800lm	670 €	3 yrs
BC9306BP-25		70 minute				25W	3300lm	670 €	3 yrs
BC9306AS-L40-15	Normal illuminate+E	140 minute				40W	1800lm	701 €	3 yrs
BC9306AS-L40-25		70 minute				40W	3300lm	701 €	3 yrs
BC9306BS-15	Only Emergency	140 minute				15W	1800lm	701 €	3 yrs

Référence	Produit		Description du produit	Driver	Angle	W	Lm	Prix € HT départ/unité	Années de garantie
BC9306BS-25		70 minute				25W	3300lm	701 €	3 yrs
BC9307P-L100 (100W LED, pole mounting)			Product name:Explosion-proof LED lamp Ex Marking:Ex db e IIC T6...T3 Gb Ex tb IIC T8°c...T195°c Db ,IP66 Cable entry:M20 M25 NPT3/4 NPT1/2 light source: Citizen 1pc Input voltage: AC90-264VAC temperature(CCT):5000k light source service life:50,000 hrs material:Special Aluminium Alloy size:300mm*290mm Net weight:6.4kgs Certificae: CE,ATEX,CNEX	Light Driver: Taiwan Meanwell	25°/40°/ 60° / 80°, 100°/ /200°, /60*80°, 90°*110°	100W	11500lm	1 000 €	5yrs
BC9307P-L120 (120W LED, pole mounting)				120W		13200lm	1 140 €	5yrs	
BC9307P-L150 (150W LED, pole mounting)				150W		16800lm	1 238 €	5yrs	
BC9307P-L180 (180W LED, pole mounting)				180W		20160lm	1 327 €	5yrs	
BC9307P-L200 (200W LED, pole mounting)				200W		23700Lm	1 393 €	5yrs	
BC9307P-L240 (240W LED, pole mounting)				240W		29100lm	1 490 €	5yrs	
BC9307P-L100-18 (100W LED, pole mounting)							Product name:Explosion-proof LED lamp Ex Marking:Ex db e IIC T6...T3 Gb Ex tb IIC T80°c...T195°c Db ,IP66 Cable entry:M20 M25 NPT3/4 NPT1/2 light source: Citizen 1pc Input voltage: AC90-264VAC temperature(CCT):5000k light source service life:50,000 hrs material:Special Aluminium Alloy size:300mm*290mm Net weight:6.8kgs Certificae: CE,ATEX,CNEX	Light Driver: Taiwan Meanwell	18°
BC9307P-L120-18 (120W LED, pole mounting)	120W	13200lm	1 204 €		5yrs				
BC9307P-L150 -18 (150W LED, pole mounting)	150W	16800lm	1 303 €		5yrs				
BC9307P-L180-18 (180W LED, pole mounting)	180W	20160lm	1 393 €		5yrs				
BC9307P-L200 -25 (200W LED, pole mounting)	200W	23700Lm	1 456 €		5yrs				
BC9307P-L240 -25 (240W LED, pole mounting)	240W	29100lm	15 545 €		5yrs				
BC9307S-L100 (100W LED, bracekt mounting)			Product name:Explosion-proof LED lamp Ex Marking:Ex db e IIC T6...T3 Gb Ex tb IIC T80°c...T195°c Db ,IP66 Cable entry:M20 M25 NPT3/4 NPT1/2 light source: Citizen 1 pc Input voltage: AC90-264V		Light Driver: Taiwan Meanwell			25°/40°/ 60° / 80°, 100°/	
BC9307S-L120 (120W LED, bracekt mounting)				120W	13200lm	1 177 €	5yrs		
BC9307S-L150 (150W LED, bracekt mounting)				150W	16800lm	1 279 €	5yrs		

Référence	Produit	Description du produit	Driver	Angle	W	Lm	Prix € HT départ/unité	Années de garantie
BC9307S-L180 (180W LED, bracekt mounting)		temperature(CCT):5000k light source service life:50,000 hrs material:Special Aluminium Alloy size:295mm*330mm*350mm Net weight:7.5kgs Certificae: CE,ATEX,CNEX	Light Driver: Inventronics	180°, /200°, /60*80°, 90°*110°	180W	20160lm	1 366 €	5yrs
BC9307S-L200 (200W LED, bracekt mounting)					200W	23700Lm	1 429 €	5yrs
BC9307S-L240 (240W LED, bracekt mounting)					240W	29100lm	1 526 €	5yrs
BC9307S-L100 -18 (100W LED, bracekt mounting)		Product name:Explosion-proof LED lamp Ex Marking:Ex db e IIC T6...T3 Gb Ex tb IIC T80°c...T195°c Db ,IP66 Cable entry:M20 M25 NPT3/4 NPT1/2 light source: Citizen 1pc Input voltage: AC90-264V temperature(CCT):5000k light source service life:50,000 hrs material:Special Aluminium Alloy size:341mm*330mm*350mm Net weight:7.5kgs Certificae: CE,ATEX,CNEX	Light Driver: Taiwan Meanwell	18°	100W	11500lm	1 097 €	5yrs
BC9307S-L120 -18 (120W LED, bracekt mounting)					120W	13200lm	1 238 €	5yrs
BC9307S-L150 -18 (150W LED, bracekt mounting)					150W	16800lm	1 339 €	5yrs
BC9307S-L180 -18 (180W LED, bracekt mounting)					180W	20160lm	1 429 €	5yrs
BC9307S-L200 -25 (200W LED, bracekt mounting)					200W	23700Lm	1 490 €	5yrs
BC9307S-L240-25 (240W LED, bracekt mounting)					240W	29100lm	1 589 €	5yrs
BC9309P-L300-18°			Light Driver: Taiwan Meanwell	18°	2X150W	34600LM	1 753 €	5yrs
BC9309P-400-25°		Product name:Explosion-proof LED lamp Ex Marking:Ex II3 G Ex nR IIC T4...T3Gc II2 D Ex tb IIC T130°c...T195°c Db Cable entry:M20,M25,NPT1/2",NPT3/4" light source: Citizen 2 pieces Rated voltage: 100~277VAC Vtemperature(CCT):5000k light source service life:50000 hrs material:Special Aluminium Alloy size:295mm*330mm*350mm	Light Driver: Inventronics	25°	2X200W	46600LM	2 166 €	5yrs
BC9309P-480-25°			Light Driver: Taiwan Meanwell		2X240W	56800LM	2 708 €	5yrs

Référence	Produit	Description du produit	Driver	Angle	W	Lm	Prix € HT départ/unité	Années de garantie
BC9309P-L240		size:200mm*200mm*60mm Net weight:11.2kgs Certificae: CE,ATEX,CNEX	Light Driver: Taiwan Meanwell		2X120W	27200LM	1 549 €	5yrs
BC9309P-L300					2X150W	34600LM	1 718 €	5yrs
BC9309P-L360			Light Driver: Inventronics		2X180W	35040LM	1 875 €	5yrs
BC9309P-L400					2X200W	46600LM	2 126 €	5yrs
BC9309P-L480				Light Driver: Taiwan Meanwell		2X240W	56800LM	2 667 €
BC9309S-L240		Product name:Explosion-proof LED lamp Ex Marking:Ex II3 G Ex nR IIC T4...T3Gc II2 D Ex tb IIIC T130°C...T195°C Db Cable entry:M20,M25,NPT1/2",NPT3/4" light source: Citizen 2 pieces Rated voltage: 100~277VAC Vtemperature(CCT):5000k light source service life:50000 hrs material:Special Aluminium Alloy size:295mm*330mm*350mm Net weight:13kgs Certificae: CE,ATEX,CNEX	Light Driver: Taiwan Meanwell		2X120W	27200LM	1 589 €	5yrs
BC9309S-L300					2X150W	34600LM	1 747 €	5yrs
BC9309S-L400			Light Driver: Inventronics		2X200W	46600LM	2 166 €	5yrs
BC9309S-L480			Light Driver: Domestics		2X240W	56800LM	2 661 €	5yrs
BC9309S-L240-18°		Product name:Explosion-proof LED lamp Ex Marking:Ex II3 G Ex nR IIC T4...T3Gc II2 D Ex tb IIIC T130°C...T195°C Db Cable entry:M20,M25,NPT1/2",NPT3/4" light source: Citizen 2 pieces Rated voltage: 100~277VAC	Light Driver: Taiwan Meanwell		2X120W	27200LM	1 631 €	5yrs
BC9309S-L300-18°					2X150W	34600LM	1 794 €	5yrs
BC9309S-L400-25°		Vtemperature(CCT):5000k light source service life:50000 hrs material:Special Aluminium Alloy size:295mm*330mm*350mm Net weight:14kgs	Light Driver: Inventronics		2X200W	46600LM	2 207 €	5yrs
BC9309S-L480-25°			Light Driver: Taiwan Meanwell		2X240W	56800LM	2 749 €	5yrs
 BC9101-L25		Ex code:Ex II2 GD, Ex d II B T6 Gb ,Extb IIIC T80°C Db IP66 Product name:Explosion Proof Floodlight light source: CREE LED 12pcs Input voltage: 90 to 305VAC light source life: 100,000 hours size: 326x326x75mm net weight:9kg material: aluminium alloy,tempered glass Certificae: CE Rohs,ATEX,IECex,CNEX	Taiwan meanwell led dirver	140°x120°	25W	2800 lm	502 €	3 yrs
 BC9101-L40					40W	4200 lm	621 €	3 yrs
 BC9101-L60					60W	5900lm	674 €	3 yrs
 BC9101-L80					80W	7200 lm	743 €	3 yrs

Référence	Produit	Description du produit	Driver	Angle	W	Lm	Prix € HT départ/unité	Années de garantie
 BC9303-L25H		Ex code:Ex II2 GD, Ex d II B T6 Gb ,Extb IIIC T80°c Db IP66 Product name:Explosion Proof Lamp light source: CREE LED 12PCS Taiwan meanwell led driver Input voltage: 90 to 264VAC (25W,40 can produce 18-43VAC/18-55VDC) light source life: 100,000 hours size: 240X240X155mm net weight: 5kg material: aluminium alloy, tempered glass ATEX certificate No.INERIS13ATEX0034X ; CE,ROHS	Taiwan meanwell led driver	140°	25W	2400 lm	352 €	3 yrs
 BC9303-L4H				140°	40W	4300lm	475 €	3 yrs
 BC9303-L60H				140°	60W	5800 lm	511 €	3 yrs
 BC9303-L25L				140°	25W	2400 lm	352 €	3 yrs
 BC9303-L40L				140°	40W	4300lm	475 €	3 yrs
 BC9700-L200		Ex code: Ex II2 GD, Ex db II C T5...T3 Gb ,Extb IIIC T95°c .. T195°c Db Product name:Explosion Proof Lamp light source:Citizen 1PC Input voltage: 90-305VAC light source service life:50,000 hrs anti corrosion grade:WF2 material: aluminium alloy size:300x300x190mm weight:6.3kg ATEX certificate No.EPT 16ATEX 2483X ;CE,IECEX	Light Driver: Inventronics	40°/ 60°/ 80°/100°// 60*80° 90°*110°	200W	24000lm	1 199 €	5yrs
 BC9700-L180					180W	20700lm	1 082 €	5yrs
 BC9700-L150			Taiwan meanwell led driver		150W	17200lm	1 017 €	5yrs
 BC9700-L120					120W	13500lm	920 €	5yrs
 BC9700-L100					100W	11700lm	830 €	5yrs
 BC9700-L80					80W	8900lm	716 €	5yrs
 BC9700-L60					60W	6600lm	601 €	5 yrs
 BC5200					 Explosion Proof Emergency Light	light source: LED Ex code:Ex II 2G Ex db ib IIC T6 Gb II 2D Ex tb IIIC T80°C Db IP66 rated power: 2x0.5W rated wattage: 220V emergency duration: 1.5hours light output:100Lumen light source life: 50,000 hours size: 295x150x275mm net weight:3.4kg material: aluminium alloy		
 BC4200	 Explosion proof Exit Sign	Product name:LED Explosion proof exit light Marking:Ex de IIB T6 Gb light source: SMD wattage:normal:3w,emergency 1w rated voltage: 220vac material: aluminium alloy size:165x374x65.5mm weight:3.8kg				185 €	3yrs	